

 EVNISKO

# EVNISKO HOME3

Mode3 22Kw AC - עמדת טעינה ביתית תלת-פאזית TYPE2

## מפרט טכני



שירות ואחריות  
NISKO

שליטה באפליקציה  
BLUETOOTH 

התקן זליגה מובנה DC 

טל.ח | התמונות להמחשה בלבד



**\*2650**   
מוקד שירות EVNISKO HOME

קבוצת ניסקו בע"מ  
המע"ן 41 מודיעין  
[www.evnisko.com](http://www.evnisko.com)  
[www.niskoelec.com](http://www.niskoelec.com)

**NISKO**  
GROUP

# EVNISO HOME3

## מפרט טכני

### POWER INPUT

AC EV charger

INPUT VOLTAGE	<b>3</b> phase 3x400VAC 50/60Hz
INPUT CURRENT	<b>3</b> phase 3x32A

### POWER OUTPUT

OUTPUT POWER	22 kW
OUTPUT TYPE	Type2 Cable (Mode 3)
CABLE LENGTH	5 meters
TYPE OF CABLES	STRAIGHT TPU
SIMULTANEOUS CHARGING	<b>1</b>

### USER INTERFACE AND CONTROL

USER INTERFACE	LED status indicator
	PLUG & CHARGE
ACCESS CONTROL	RFID (Mifare ISO & IEC 14443A) App with BLE (Default)

### CONNECTIVITY

COMMUNICATION INTERFACE	BLUETOOTH
	RFID IEC 1444 3A

### CERTIFICATE

VERSION	EN/IEC 61851-1:2019, EN/IEC 61851-21-2:2018, IEC 62955:2018
---------	---

### SAFETY PROTECTIONS

OVER CURRENT PROTECTION, RESIDUAL CURRENT PROTECTION, GROUND PROTECTION, OVER/UNDER VOLTAGE PROTECTION, SURGE PROTECTION, OVER/UNDER TEMPERATURE PROTECTION

### PHYSICAL

MOUNTING METHOD	WALL-mounted POLE-mounted
ENCLOSURE	Plastic
DIMENSIONS (LxWxH)	PRODUCT 255x100x324mm PACK 460x280x220mm
WEIGHT	NET 5.8Kg GROSS 6.5Kg

### ENVIRONMENTAL

OPERATING TEMPERATURE	-30°C to +55°C
INSTALLATION	INDOOR / OUTDOOR
HUMIDITY	MAX.95% (non-regulating)

### STANDARDS

CONFORMITY	IEC 61851-1
DEGREE OF PROTECTION	IP65
IMPACT STRENGTH	IK08
EARTH FAULT PROTECTION	30 mA AC TypeA + 6 mA DC RCD
STANDBY POWER	<3W
MEASURING ACCURACY	1%
COOLING	Natural cooling
WARRANTY	<b>2 YEARS</b>